



Thomas Grinding, Inc.

Manufacturers of quality grinding equipment since 1993

P.O. Box 1083
Moore Haven, FL 33471
(863) 946-1461
Fax: (863) 946-1448


Call us toll free: 1-888-385-5023

STUMP EATER MODEL 250-44 #SG44-0105

- **GENERAL: FUEL TANK : REMOTE MOUNTED 197 GAL. W/FILTER SEPARATOR (OPTION TO TIE INTO CARRIER FUEL SYSTEM)**
- **RADIATOR: EXTREME DUTY WITH TRASH GUARD**
- **AIR CLEANER: 2 STAGE HEAVY DUTY**
- **ELECTRICAL: 12 VOLT SYSTEM 1200 SERIES BATTERIES**
- **CONTROL SYSTEM: MURPHY ELECTRONIC CONTROL CENTER WITH LODAR REMOTE CONTROL WIRELESS HAND HELD CONTROL WITH IDLE UP AND DOWN WITH HOLD FEATURE AND EMERGENCY SHUTDOWN ALL FROM THE COMFORT OF YOUR CAB.**
- **WEIGHT: APPROXIMATE 9,000 LBS WITH STAND**
- **FRAME: WIDTH 73" HEIGHT (OVERALL) 100" LENGTH 78"**
- **PTO: TWIN DISC**
- **SUPER HEAVY DUTY FRAME CONSTRUCTION WITH DOUBLE TAPER ROLLER BEARINGS**
- **LOW MAINTENANCE (ONLY 4 BEARINGS TO GREASE) AND LONG LASTING EASY TO MAINTAIN BELT SYSTEM. (THE MOST FORGIVING SYSTEM IN CASE OF ACCIDENTAL BINDING.**
- **ENGINE: CAT® PROVEN DEPENDABILITY & PERFORMANCE
TYPE-3126B TIER II CATERPILLAR**
- **6 CYLINDERS AIR TO AIR COOLED TURBO CHARGED**

- **RATED POWER: 250 HP @ 2100 RPM**
- **GOVERNING ELECTRONIC**
- **ENGINE PROTECTION: LOW OIL PRESSURE, HIGH WATER TEMPERATURE SHUTDOWN**
- **CUTTING DISC:**

SANDVIC DURA Disk™ II Stump Cutting System®



(1) Long Plow Bolt Bit

The same Long Plow Bolt Bit is used on both sides of the disk. This simplifies tool replacement and enables you to move a worn bit to the other side of the disk for additional use. The use of thicker harder carbide tips, increase durability and wear resistance. This keeps tools sharper longer.

(2) Long Plow Bolt Bit Pocket

The same plow bolt bit pocket is used on both sides of the disk. This simplifies tool replacement and enables you to move a worn pocket to the other side of the disk for additional use. The plow bolt design of the bit and pocket index the bits automatically and prevent rotation.

(3) Short Plow Bolt Bit

The short plow bolt bit utilizes the same features as the long plow bolt bit (see item #1).

(4) Short Plow Bolt Bit Pocket

The short plow bolt pocket provides automatic positioning and gaging for the short plow bolt bit.

- **REPLACEMENT TOOLING**

QTY

- R1CX-1626-7566 SHORT TEETH 20
- R1CT-1626-7566 LONG TEETH 96
- 2020NUT NUTS 116
- M8D-0044 POCKET, BOLT ON 96

- DIMENSION W/O TEETH 1.5" X 44"

- DISC SPEED W/ ENGINE @ 2000 RPM 383 RPM @ 2200 IS 420 RPM

- DISC MOUNTING 4" THROW SHAFT MOUNTED ON H.D. DOUBLE ROLLER FLANGE BEARINGS

- USABLE CUTTING SURFACE 15" BOTH SIDES EQUAL

- DEPTH UNLIMITED WITH MULTIPLE PASSES

- EXCAVATOR MOUNTED (BUSHING KIT AVAILABLE FOR DIFFERENT SIZE BUCKET PINS)

- MIN EXCAVATOR SIZE: 20 METRIC TON 45,000 LB OR LARGER EXCAVATOR.
NOTE AUX. FUEL TANK 197 GAL OPTIONAL MOUNTED ON REAR OF EXCAVATOR.
GRINDER CAN ALSO BE PLUMBED DIRECT TO EXCAVATORS FUEL SOURCE.

- SHAFTS: ALL CONSTRUCTED FROM 4140 HEAT TREAT MATERIAL
PTO CLUTCH SHAFT 2 7/16" , JACK SHAFT 3 7/16", DISC SHAFT 4 7/16"